Safety Data Sheet



Section 1: Identification

Product identifier				
Product Name	Start Your Engine Aerosol			
Synonyms	595002			
Product Code	21214			
Relevant identified uses o	f the substance or mixture and uses advised against			
Recommended use	No data available			
Details of the supplier of t	he safety data sheet			
Manufacturer	Gold Eagle Co.			
	4400 S. Kildare Avenue Chicago, IL 60632-4372 United States http://www.goldeagle.com/			
Telephone (General) •	773-376-4400			
Emergency telephone number				
Manufacturer	1-800-535-5053 - (INFOTRAC #22283)			

Section 2: Hazard Identification

United States (US) According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012	 Skin Irritation 2 Eye Mild Irritation 2B Flammable Aerosols 1 Acute Toxicity Oral 4 Acute Toxicity Dermal 4 Acute Toxicity Inhalation 4 Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation Specific Target Organ Toxicity Repeated Exposure 2 Flammable Liquids 1
---------------	--

Label elements **OSHA HCS 2012**

DANGER



Hazard statements · Extremely flammable aerosol Contains gas under pressure; may explode if heated Causes skin irritation Causes eye irritation

	Harmful if swallowed Harmful in contact with skin Harmful if inhaled Extremely flammable liquid and vapour May cause respiratory irritation May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
Prevention •	Keep away from heat, sparks, open flames and/or hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Keep out of reach of children. Read label before use. Do not eat, drink or smoke when using this product. Avoid breathing dust, fume, gas, mist, vapours and/or spray. Use only outdoors or in a well-ventilated area. Use only non-sparking tools. Wear respiratory protection. Ground and/or bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Take precautionary measures against static discharge. Do not breathe dust, fume, gas, mist, vapours and/or spray. Wear face protection . Wear protective gloves . Use personal protective equipment as required. Do not expose to temperatures exceeding 50 oC/122oF.
Response •	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,
	 if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Take off contaminated clothing and wash before reuse. Specific treatment is urgent, see supplemental first aid information. Get medical advice/attention if you feel unwell. Evacuate area.
Storage/Disposal •	Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. Store locked up. Maintain air gap between stacks and/or pallets. Store in a well-ventilated place. Keep cool.
Other hazards	
	No data available

OSHA HCS 2012

· No data available

Other information



Section 3 - Composition/Information on Ingredients

Substances

Mixtures

Composition						
Chemical Name	Identifiers	%	Hazardous	LD50/LC50	LC50 Classifications According to Regulation/Directive	
Xylene	CAS :1330-20-7	0% TO 20%	No	NDA	OSHA HCS 2012: Skin Irrit. 2; Eye Irrit. 2; Acute Tox. Inhal. 4; STOT SE 3: Narc.; STOT SE 3: Resp. Irrit.; Flam. Liq. 3; Repr. 1B	
Isopropyl alcohol	CAS: 67-63- 0	0% TO 20%	No	NDA	OSHA HCS 2012: Eye Irrit. 2; Skin Sens. 1B; Asp. Tox. 1; STOT RE 1; STOT SE 3: Narc.; STOT SE 3: Resp. Irrit.; Flam. Liq. 2; Repr. 2	
Butane	CAS :106-97 -8	0% TO 5%	No	NDA	OSHA HCS 2012: Simp. Asphyx.; STOT SE 3: Narc.; Flam. Gas 1; Press. Gas - Comp	
Meth Tert Butyl Ether	CAS :1634- 04-4	0% TO 50%	No	NDA	OSHA HCS 2012:	
Propane	CAS :74-98- 6	0% TO 10%	No	NDA	OSHA HCS 2012: Simp. Asphyx.; Flam. Gas 1; Press. Gas - Liq.	

Section 4: First-Aid Measures

Description of first aid measures

Inhalation	 Get medical attention immediately. Give artificial respiration if victim is not breathing. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a
Skin	 position comfortable for breathing. After contact with skin, take off immediately all contaminated clothing and wash immediately with plenty of fresh water. If irritation develops and persists, get medical attention. If skin irritation occurs: Get medical advice/attention.
Eye	• IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. If swallowed, DO NOT induce vomiting. Get medical attention immediately.
Most important symptom	ms and effects, both acute and delayed
	 Refer to Section 11 - Toxicological Information.
Indication of any immed	liate medical attention and special treatment needed
Notes to Physician	 All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.
Section 5: Fire-Fighting	y Measures

Extinguishing media	
Suitable Extinguishing Media	 LARGE FIRE: Water spray, fog or regular foam. SMALL FIRES: CO2, dry chemical, dry sand, alcohol-resistant foam.
Unsuitable Extinguishing Media	No data available.
Firefighting Procedures	As an immediate precautionary measure, isolate spill or leak area for at least 50
Preparation Date: 07/October/2016	Format: GHS Language: English (US)

L H S V G	neters (150 feet) in all directions. ARGE FIRES: Dike fire-control water for later disposal. Keep out of low areas. Keep unauthorized personnel away. Stay upwind. /entilate closed spaces before entering. CAUTION: All these products have a very low flash point: Use of water spray when ighting fire may be inefficient. CARGO FIRES: DO NOT fight fire when fire reaches cargo! Cargo may EXPLODE!

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards	•	Contains gas under pressure; May explode if heated. Extremely Flammable Aerosol. Vapors may travel to source of ignition and flash back. When heated, vapors may form explosive mixtures with air: indoors, outdoors and sewers explosion hazards. Containers may explode when heated. Explosive; severe projection hazard. May be ignited by friction, heat, sparks or flames. Vapors may form explosive mixtures with air. Vapor explosion hazard indoors, outdoors or in sewers.
Hazardous Combustion Products	•	Vapors form explosive mixtures with air: indoors, outdoors and sewers explosion hazards.
Advice for firefighters		
	•	Fire fighters should wear complete protective clothing including self-contained breathingapparatus. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

· • • • • • • • • • • • • • • • • • • •			
Personal Precautions	 Do not walk through spilled material. Avoid contact with skin, eyes, and clothing. Ventilate the area. Do not breathe mist, vapours and/or spray. Wear a self-contained breathing apparatus and appropriate Personal Protective Equipment (PPE) 		
Emergency Procedures	 As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Keep out of low areas. Keep unauthorized personnel away. Stay upwind. Ventilate closed spaces before entering. 		
Environmental precautions			
	 Avoid run off to waterways and sewers. Prevent spreading of vapors through sewers, ventilation systems and confined areas. Runoff from fire control or dilution water may cause pollution. 		
Methods and material fo	or containment and cleaning up		
Methods and material for containment and cleaning up Containment/Clean-up Measures • LARGE SPILLS: Dike far ahead of spill for later disposal. SMALL SPILLS: Take up with sand or other non-combustible absorbent materia place into containers for later disposal. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE) DO NOT CLEAN-UP OR DISPOSE OF, EXCEPT UNDER SUPERVISION OF A SPECIALIST Use clean non-sparking tools to collect absorbed material.			

Section 7 - Handling and Storage

Precautions for safe handling

Handling

 Keep away from fire - No Smoking. Avoid contact with heat and ignition sources. Avoid contact with skin, eyes, and clothing. Keep from direct sunlight. Wear appropriate personal protective equipment, avoid direct contact. Do not breathe mist, vapours and/or spray.

Conditions for safe storage, including any incompatibilities

Storage

Store in a well-ventilated place, do not store above 120 F. Store in a cool, dry, well-ventilated place. Avoid shock, impact, friction, and rough handling. Keep away from sources of ignition, flammable, oxidizing materials, and acids. No smoking in area of storage.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure Limits/Guidelines • No data available.

Exposure controls

Engineering Measures/Controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use only appropriately classified electrical equipment.

Personal Protective Equipment

Pictograms



Respiratory	 Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.
Eye/Face	Wear safety glasses.
Hands	 Wear protective gloves/protective clothing/eye protection/face protection.
Skin/Body	 Wear protective gloves/protective clothing/eye protection/face protection. Wear synthetic apron.
General Industrial Hygiene Considerations	 Avoid contact with skin and eyes. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Handle in accordance with good industrial hygiene and safety practice.
Environmental Exposure Controls	 Follow best practice for site management and disposal of waste.

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Aerosol	Appearance/Description	No data available
Color	No data available	Odor	Solvent
Taste	No data available	Particulate Type	No data available
Particulate Size	No data available	Aerosol Type	Spray
Odor Threshold	No data available	Physical and Chemical Properties	Water white to pale yellow liquid.
General Properties			
Boiling Point	-42 °C(-43.6 °F)	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	Heat of Decomposition	No data available
рН	No data available	Specific Gravity/Relative Density	No data available
Density	No data available	Bulk Density	No data available
Water Solubility	No data available	Solvent Solubility	Poorly soluble in water

Viscosity	No data available	Explosive Properties	No data available					
Oxidizing Properties:	No data available							
Volatility	/olatility							
Vapor Pressure	1.5 psi @ 20 °C(68 °F)	Vapor Density	No data available					
Evaporation Rate	No data available	VOC (Wt.)	No data available					
VOC (Vol.)	93.3 %	Volatiles (Wt.)	No data available					
Volatiles (Vol.)	100 %							
Flammability	Flammability							
Flash Point	-23 °C(-9.4 °F) TCC (Tagliabue Closed Cup)	UEL	No data available					
LEL	No data available	Autoignition	No data available					
Self-Accelerating Decomposition Temperature (SADT)	No data available	Heat of Combustion (ΔHc)	No data available					
Burning Time	No data available	Flame Height	No data available					
Flame Extension	No data available	Ignition Distance	No data available					
Flame Duration	No data available	Flammability (solid, gas)	Level 3 aerosol.					

Other Information

Section 10: Stability and Reactivity

• Vapor density is heavier than air. Evaporation rate is slower than ether.

	,
Reactivity	
	 Extremely flammable aerosol. Contains gas under pressure, may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition. Extremely flammable liquid and vapor. May form flammable/explosive vapor/air mixture.
Chemical stability	
	 Stable under normal temperatures and pressures.
Possibility of hazardous	s reactions
	 Hazardous polymerization not indicated.
Conditions to avoid	
	 Keep away from heat, sparks, and flame.
Incompatible materials	
	 Strong acids. Strong oxidizing agents, amines, chlorinated compounds, and caustic materials.
Hazardous decomposit	ion products
-	No data available

Section 11 - Toxicological Information

Information on toxicological effects

ssification		
OSHA HCS 2012 • Acute Toxicity - Dermal 4; Acute Toxicity - Inhalation 4; Acute Toxicity - Oral 4		
OSHA HCS 2012 • Skin Irritation 2		

Serious eye damage/Irritation	OSHA HCS 2012 • Eye Mild Irritation 2B		
Skin sensitization	OSHA HCS 2012 • Data lacking		
Respiratory sensitization	OSHA HCS 2012 • Data lacking		
Aspiration Hazard OSHA HCS 2012 • Classification criteria not met			
Carcinogenicity	OSHA HCS 2012 • Data lacking		
Germ Cell Mutagenicity	OSHA HCS 2012 • Data lacking		
Toxicity for Reproduction	OSHA HCS 2012 • Classification criteria not met		
STOT-SE	OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Respirato Tract Irritation		
STOT-RE	OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 2		

Potential Health Effects

Acute (Immediate) Chronic (Delayed)

Acute (Immediate)

Chronic (Delayed)

Acute (Immediate)

Chronic (Delayed)

Inhalation Acute (Immediate) Chronic (Delayed)

- No data available
- Under normal conditions of use, no health effects are expected.

Skin

Eye

Ingestion

•	May	cause	mild	irritation.
---	-----	-------	------	-------------

- Under normal conditions of use, no health effects are expected.
- Causes eye irritation.
 - Under normal conditions of use, no health effects are expected.
 - May cause irritation. Under normal conditions of use, no health effects are expected.
 - Under normal conditions of use, no health effects are expected.

Section 12 - Ecological Information

Toxicity	
	No data available
Persistence and degrada	bility
	 Non-mandatory section - information about this substance not complied for this reason.
Bioaccumulative potentia	l l
	 Non-mandatory section - information about this substance not complied for this reason.
Mobility in Soil	
	 Non-mandatory section - information about this substance not complied for this reason.
Other adverse effects	
	 Non-mandatory section - information about this substance not complied for this reason.
Ecological Fate	No data available.
Potential Environmental Effects	No data available.

Section 13 - Disposal Considerations			
Waste treatment methods			
Product waste	 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. 		
Packaging waste	 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. Flammable vapors may accumulate in the container. Handle empty containers with care because residual vapors are flammable. 		
Other Information			
	 Avoid release to the environment. Use of this chemical in areas where soils are permeable, particularly where the water table is shallow, may result in ground-water contamination. 		

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	1950	Aerosols flammable, n.o.s.(each not exceeding 1L capacity)	2.1		Not Applicable
0	Special presentions for year				

Special precautions for user • No data available

Transport in bulk according • No data available to Annex II of MARPOL 73/78 and the IBC Code

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Fire, Pressure(Sudden Release of)

they are appropriate.

Section 16 - Other Information		
Revision Date	• 10/March/2017	
Preparation Date	• 07/October/2016	
Other Information	Schedule B Number: 2909.19.1400.	
Disclaimer/Statement of Liability	 Information presented herein is believed to be factual, as it has been derived from the works and opinions of persons believed to be qualified experts. However, nothing contained in this information is to be taken as warranty or representation for which the 	

Gold Eagle Co. bears legal responsibility. The user should review any

recommendations in the specific context of the intended use to determine whether